

Ultra PTFE

High performance PTFE lubricant, multipurpose, extreme conditions, rust dissolver for automotive, bicycles, industry and construction



Ultra-PTFE is a very high quality, multipurpose PTFE-based lubricant. Resistant to low and high temperatures up to +250°C, it keeps its long-lasting lubricant power.

With its perfect adhesion on almost any surface, **Ultra-PTFE** is suitable for chains that are exposed to extreme conditions, mechanisms, gears and all moving or hinged parts. The addition of PTFE allows a smooth and fluid lubrication.

Ultra-PTFE dissolves rust and dirt within a few seconds and keeps its high penetrating power and lubrication through corroded surfaces.

Ultra-PTFE can be used as lubrication in lathes in the field of cycles, automotive and industry. For all weather conditions and very low or high temperatures.

Aerosol 500 ml

Main applications for Ultra PTFE :

- Multipurpose PTFE lubricant
- Reduces wear on chains and increase their lifespans
- High lubricating power in extreme conditions of all kinds of chains, cogs and bearings for bikes, motorbikes, chainsaws, machines, boats, tractors,
- lubrication of cables, mechanisms, conveyors belts, gearwheels, pumps, rails, hinges, cranks
- lubrication of locks and pneumatic tools, all moving parts
- Long lasting lubrication up to +250°C, for very low and high temperatures
- Dissolves rust and dirt
- High adhesion power and strong and deep penetrating effect
- Non-corrosive and water-resistant
- Lubricant for all rusted surfaces

Instructions of use of Ultra PTFE :

- Shake thoroughly the aerosol before use
- Spray from a distance of 15-20 cm
- All surfaces could be cleaned with **Ultra-Cleaner**
- Keep away from children

Technical information of Ultra PTFE :

- Packaging : aerosol 500 ml
- Colour : transparent/white
- Viscosity : 100 cst
- Change in condition/boiling point : approximately 280°C
- Auto-ignition temperature : 200°C DIN 51794
- Flash point : 160°C DIN 51755
- pH value undiluted (20°C) : 12.5 DIN 19261
- Solubility in water (20°C) : insoluble
- pH (20°C) : 11.6
- Density g/ml : 0.85 g/cm³ DIN 51557
- Temperature application : up to +250°C
- Storage : in a cool dry place. Shelf life : 24 months
- Always read the safety data sheet (SDS) before use

Packaging :

Article Nr	Product	Packaging	Content	Unit	Packing
784205	Ultra PTFE	aerosol	500	ml	12

Related products of Ultra PTFE :

- **Ultra-Cleaner** Ultra-power cleaner and degreaser for automotive, bikes, motorbikes, industry and building
- **Bio-Clean** Biodegradable cleaner for automotive, bicycles, motorbikes, mechanics, building and industry
- **Power Foam** Powerful ready to use foam cleaner, all surfaces
- **Disk Cleaner** Very powerful disk and liquid brake, mechanics and engines cleaner
- **Ultra-Oil** Powerful penetrating oil, lubricant, cleaner for tar and grease, contact spray, moisture repellent
- **Ultra-Chain** High performance lubricant for chains and moving parts, antiwear and corrosion
- **Bio-Wipes** Recycled and eco-friendly cleaning wipes for grease, lubricants, dirt, painting, sealants all surfaces

Safety instructions and conditions of use of products - Liability

All given information of product sheets are established under our current knowledge and are indicated as approximate datas and should not be considered as exhaustive. Products are subject to modification without any prior information which could lead to variations of applications and performances. Always use the latest updated technical sheet. We are not responsible for any damage or loss due to information or errors in that document which are in any way not a guarantee.

Considering the large quantity of materials and supports, application methods different for each use, storage and transportation conditions which are totally out of our control, we are not liable for any damage or loss, directly or indirectly caused by the use of our products.

We strongly recommend the user to make prior testings to make sure the product is suitable for the intended application or use.

Always wearing individual safety protection equipments when using our products like gloves, long sleeves, full covering clothes, glasses, masks, etc.

The user is also informed to read the latest Safety Sheet before using our products concerning all safety instructions which are on the packaging of the product.

Always keep out of the reach of children and store products in a locked storage area.

Avoid any chemical contact during pregnancy or while nursing for the safety and the health of the baby to avoid foetal malformations.

If swallowed, immediately call a doctor or the hospital or the closest poison with the packaging of the product and/or the Safety Sheet of the product.

In case of allergy, inhalation or contact of the eyes with the product, rinse cautiously with water for several minutes or remove person to fresh air and keep comfortable for breathing and in case of emergency, contact a doctor or the hospital or the closest poison with the packaging of the product and/or the Safety Sheet of the product. Do not breath spray. Use only outdoor or in a well ventilated area.

Avoid any release to the environment. Eliminate the content and the container in the specific collection of your city in accordance with local/regional/national regulations. Harmful to aquatic life with long lasting effects.

No smoking. Keep container tightly closed. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source to avoid any burn or fire. Protect from sunlight. Store in a cool and well-ventilated place.

Safety Data Sheet on request

Iseole Sarl 23, rue du Vignoble – 68610 Lautenbach - France Tel : +33 6 38 03 05 68

Web : <https://lookanik.com>

Mail : iseole@orange.fr

RCS Colmar Sarl - capital 7500 euros N° Siret : 790 173 405 00024 APE :4619B VAT intracommun. FR 83 790173405

© Iseole Sarl All rights reserved. Any copy or reproduction of any part of this document is strictly forbidden without the written authorization of Iseole Sarl company